BEUSSE BROWNLEE WOLTER MORA & MAIRE, P.A.

RECEIVED CENTRAL FAX CENTER AUG 3 1 2005

то	FROM:			
	PASSES.			
	James H. Beusse			
Anh D. Mai	•			
Art Unit: 2814				
COMPANY:	DATT:			
U.S. Patent Office	August 31, 2005			
571-273-8300 – Central Fax No.	TOTAL NO. OF PAGES INCLUDING COVER.			
PHONE NUMBER 1-866-217-9197	SENDER'S RUFERUNCE NUMBER 075903-001			
^{RL:} 09/905,398	YOUR REFERENCE NUMBER			
L. A. A. A. C.	· · · · · · · · · · · · · · · · · · ·			
DURCHNI DE LEASE	COMMENT PI.EASE REPLY PI.EASE RECYCLE			

RESPONSE TO NOTICE OF NON-COMPLIANT APPEAL BRIEF, DATE MAILED AUGUST 10, 2005.

Please confirm receipt.

THANKS.

4079267720

	u.s.	Patent and Tr	rademark Offica: L	PTO/SB/21 (09-04) TRICHIGN 07/31/2006 OMB 0851-0031 J.S. DEPARTMENT OF COMMERCE	
Under the Pagement Reduction Act of 1995, no person	Application Number	09/905		dishiava a valid OMB control number.	
TRANSMITTAL	Filing Date	07/14/			
FORM	First Named Inventor		Layadi		
	Art Linit	2814			
(go ne used for an correspondence after inmal fung)	Examiner Name). Mai		
Total Number of Pages in This Submission	Attorney Docket Number	Attorney Docket Number Layadi 30-23/075903-001		5903-001	
ENC	CLOSURES (Check a	I that apply)		
Fee Transmittal Form	Drawing(s)			Allowance Communication to TC	
Fee Attached	Licensing-related Papers		of Appeals and Interferences		
Amenament/Roply After Final Affidavits/declaration(s) Extension of Time Request Express Abandonment Request Information Disclosure Statement. Certified Copy of Priority Document(s) Reply to Missing Parts/ Incomplete Application Reply to Missing Parts under 37 CFR 1.52 or 1.53	Petition Petition to Convert to a Provisional Application Power of Attorney, Revocate Change of Correspondence Terminal Disclaimer Request for Refund CD, Number of CD(s) Landscape Table on Carks	Address	(Apper		
SIGNATURE	OF APPLICANT, ATTO	DRNEY, C	R AGENT		
Firm Name Beusse Brownlee-Wolter Mora & Maire, P.A.					
Signature of the Sausse					
Printed name James H. Beusse					
Data August 31, 2005		Reg. No.	27,115		
CERTIFICATE OF TRANSMISSION/MAILING I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:					
Signature . Shirle And					
Typed or printed name Shirley Goff	0 008		Date	08/31/2005	

The collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to tile (and by the uSPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 14. This collection is estimated to 2 hours to complete, including gathering, proparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete mis form and/or suggestions for recurring this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademain Officer, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450, DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.Q. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application o	f:)	RECEIVED CENTRAL FAX CENTER	
)	AUG 3 1 2005	
Applicants:	Nace Layadi et al.)		
Examiner:	Mai, Amh D.)		
Serial No.	09/905,398	.)		
Filed:	07/14/2001)		
Group Art:	2814)		
Attny. Docket:	Layadi 30-23)		

For: POLISH OR ETCH STOP LAYER

Board of Patent Appeals and Interferences United States Patent and Trademark Office P.O. Box 1450 Alexandria, VA 223 13-1450

APPELLANT'S BRIEF UNDER 37 CFR 41.10

This brief is submitted in furtherance of the Notice of Appeal filed in this application on July 14, 2004; and further in response to the Notification of Non-Compliant Appeal Brief mailed on August 10, 2005.

1. REAL PARTY IN INTEREST - 37 CFR 41 .37(c)(1)(i)

The real party in interest in this Appeal is the assignee of the present application, Agere Systems, Inc., a corporation of the State of Delaware.

2. RELATED APPEALS AND INTERFERENCES - 37 CFR 41.37(c)(1)(ii)

There is no other appeal or interference that will directly affect, or that will be directly affected by, or that will have a bearing on the Board's decision in this Appeal.

3. STATUS OF CLAIMS -37 CFR 41.37(c)(1)(iii)

Claims cancelled: 6 and 8-17

(Note: two claims were erroneously numbered 16 in the original application. Because of this mistake, no claim 18 was ever presented in the application).

Claims withdrawn but not cancelled: none.

Claims pending: 1-5, 7 and 19-21.

Claims allowed: none.

Claims rejected: 1-5, 7 and 19-21.

The claims on appeal are 1-5, 7 and 21 (Claims 19-20 are not appealed)

4. STATUS OF AMENDMENTS - 41.37(c)(1)(iv)

The amendment submitted after the Final Rejection contained in the Office Communication dated 04/14/2004 has been entered and no other amendments are pending.

5. SUMMARY OF CLAIMED SUBJECT MATTER - 37 CFR 41 .37(e)(1)(v)

In general, conventional planarizing techniques in the cleaning stage of deposition are inadequate for interconnect systems with more than three layers of metal. However, global planarization of both dielectric and metal layers is possible with Chemical Mechanical Planarization (CMP) (sometimes referred to as "polishing."). Although serving as a valuable planarizing technique and offering a number of advantages, a major disadvantage known as dishing is also associated with CMP. Dishing involves the thinning of regions that are exposed when a film is being planarized down to a CMP-stop layer. Applicants have discovered that TiAlN can be used as a polish/etch stop material when deposited in a layer over a dielectric material and solves this long-felt limitation during such CMP processing, while boosting commercial success.

Claims 1 and 21 are independent claims, each of which recite a semiconductor structure having a TiAlN polish stop layer deposited over a dielectric material in order to protect the dielectric material during the polishing of a metal layer deposited over the TiAlN and dielectric. The metal layer is typically tungsten and is deposited in order to

fill vias in the dielectric material. All of the tungsten layer must be removed leaving only the tungsten plugs in the vias. FIG.'s 1 and 2 show the structure before and after planarization and are described in the specification at page 4, line 24 through page 5, line 20.

4079267720

- 6. GROUNDS OF REJECTION TO BE REVIEWED UPON APPEAL -37 CFR 41.37(c)(1)(vi)
- (A) Claims 1-5,7 and 21 are rejected under 35 USC 103(a) as being unpatentable over Yamashita (JP patent 08-107148) in view of Meikle (U.S. patent 5,231,306).

7. ARGUMENT 37 CFR 41.37(c)(1)(vii)

A) Rejection of claims 1-5, 7 and 21 under 35 USC 103(a) as being unpatentable over Yamashita (JP patent 08-107148) in view of Meikle (U.S. patent 5,231,306).

The Examiner cites Yamashita for the premise that Yamashita teaches a semiconductor device including a polish stop layer, wherein the polish stop layer comprises titanium nitride (TiN). The Examiner further discusses that in view of Meikle, titanium aluminum nitride can be used in place of the TiN layer.

The Examiner, however, admits that Yamashita fails to disclose the claim I limitation of "wherein said polish stop layer comprises titanium aluminum nitride." The Examiner states "Meikle teaches that TiAlN are known in the art to be used in place of TiN in semiconductor devices" and that "it would have been obvious to one having ordinary skill in the art at the time of invention to form the polish stop layer (30) of Yamashita using TiAlN as taught by Meikle because TiAlN material is more resistant to diffusion than TiN." According to the Examiner, "[b]y the teaching that TiAIN can replace TiN in many of its uses in (underlined by Examiner) semiconductor devices, it is more probabl[e] than not

[that] TiAlN is capable of function as a polish stop layer."

The Examiner incorrectly assumes that a polish stop layer is being used in semiconductor devices. A polish stop layer is not used in semiconductor devices but is

rather used in the fabrication of semiconductor devices. According to Meikle, "[TiAlN] can replace TiN in many of its uses in semiconductor devices." Yamashita's polish stop layer, like that of Applicant's is not being utilized "in semiconductor devices." But is used instead "in the fabrication of semiconductor devices." For this reason, Meikle's statement regarding the possible replacement of TIN with TiAlN is inapplicable to polish stop layers. Therefore, Examiner incorrectly cites Yamashita in view of Meikle.

Furthermore, MPEP 2143.01 provides: The mere fact that references can be combined or modified in hindsight does not render that resultant combination obvious. Rather, the prior art must also suggest the desirability of the combination (In re Mills, 916 F.2d 680, 16 USPQ2d 1430 (Fed. Cir. 1990)). Meikle provides a diffusion barrier comprising an alloy of titanium, nitrogen, and aluminum. However, Meikle neither teaches nor suggests that TiAlN can be used as a polish stop layer. It is well known that various different materials can be substituted for other materials in some applications but not in others. For example, tungsten serves well as a filament in a light while aluminum quickly is destroyed. Yet both of these are electrical conductors and are used as such in semiconductor structures. The examiner's logic would suggest that aluminum could function as a light filament since it can be used as an electrical conductor.

The Examiner has failed to satisfy the burden of factually supporting the prima facie conclusion of obviousness as set forth in MPEP 2142. For TiAlN to be employed in Meikle's diffusion barrier as well as in Applicant's polish stop layer is simply nonobvious. A diffusion barrier is unlike a polish stop layer. A diffusion barrier is used directly within a semiconductor device to resist molecular diffusion between two interfaces. Diffusion is defined as the movement of one material through another via a natural chemical process. As Meikle describes, a diffusion barrier is used in the semiconductor device to prevent interdiffusion of a metal and silicone interface, which will occur over time even at room temperature. Applicant, on the other hand, teaches the use of TiAlN during the stage of Chemical Mechanical Planarization (CMP) for fabricating a semiconductor device. While Applicant uses TiAlN during the process of fabricating a semiconductor device, Meikle uses TiAlN to ultimately operate within a finished semiconductor device. Meikle, therefore, does not teach, suggest or motivate the use of TIALN as a polish stop layer.

Prima facie obviousness also requires a reasonable expectation of success. In re-

Clinton, 188 USPQ 365. Meikle's teaching regarding the performance of TiAlN for preventing interdiffusion of silicon and aluminum at a silicon/aluminum interface provides no basis for any expectation regarding the performance of that material as a polish stop layer. Furthermore, the fact that Meikle teaches TiAlN is more resistant to diffusion than TiN provides no motivation for using titanium nitride alloyed with aluminum in place of titanium nitride as a polish stop layer.

4079267720

The Examiner has failed to satisfy the burden of factually supporting the prima facie conclusion of obviousness as required under MPEP 2142. First, the Examiner describes the teaching of Yamashita and states "wherein the barrier layer (27) functions as an etch stop layer. (See Fig. 6)." This is technically incorrect, since layer 27 of Yamashita has clearly been partially etched away during the dielectric-etching step illustrated in FIG. 5. Thus, Yamashita actually teaches that the material of layer 27, which is titanium nitride, will not function as an etch stop layer.

Meikle states at column 2, lines 35-36 that "TiAlN etches readily in NH₄OH/H₂O₂ similar to TiN." Thus Meikle fails to recognize the significantly different etch properties of these two materials. Accordingly, it is not proper to combine Yamashita and Meikle since the substitution of titanium nitride alloyed with aluminum from Meikle into the layer 27 of Yamashita would interfere with the etching step of FIG. 5 of Yamashita wherein a portion of that layer is intentionally removed. Thus, the combination of the teaching of Meikle into the device of Yamashita would not result in the intended structure of FIG. 6 of Yamashita, thereby destroying the intent of the Yamashita patent.

Claim 21 includes the limitations of "a layer of titanium aluminum nitride disposed of the metal layer" and "wherein the layer of titanium aluminum nitride function as an etch stop layer upon removal of the selected portion of the dielectric layer to prevent the etching process from compromising the underlying metal layer." The combination of Yamashita and Meikle fails to establish a prima facie case for the obviousness of this claimed combination.

While the ultimate conclusion of obviousness is for the court to decide as a matter of law, several factual inquiries underlie this determination. <u>Graham v. John Deere Co.</u>, 383 U.S. 1, 17-18, 15 L. Ed. 2d 545, 86 S. Ct. 684 (1966). These inquiries include the scope and content of the prior art, the level of ordinary skill in the field of

the invention, the differences between the claimed invention and the prior art, and any objective evidence of nonobviousness such as a long-felt need and commercial success. Id., Akamai Techs. v. Cable & Wireless Internet Servs., 344 F.3d 1186, 1195-1196 (Fed. Cir., 2003).

When a rejection depends on a combination of prior art references, there must be some teaching, suggestion, or motivation to combine the references. <u>In re Geiger</u>, 815 F.2d 686, 688 (Fed. Cir. 1987), Although the suggestion to combine references may flow from the nature of the problem, <u>Pro-Mold & Tool Co. v. Great Lakes Plastics. Inc.</u>, 75 F.3d 1568, 1573 (Fed. Cir. 1996), the suggestion more often comes from the teachings of the pertinent references, <u>In re Semaker</u>, 702 F.2d 989, 994 (Fed. Cir. 1983), or from the ordinary knowledge of those skilled in the art that certain references are of special importance in a particular field, <u>Pro-Mold</u>, 75 F.3d at 1573 (citing <u>Ashland Oil</u>, <u>Inc. v. Delta Resins & Refractories</u>, <u>Inc.</u>, 776 F.2d 281, 297 n.24 (Fed. Cir. 1985)).

In no patents referred to by the Examiner nor in the ordinary knowledge of those skilled in the art is there any suggestion that using TiAlN as a polish stop layer would be obvious. When determining the patentability of a claimed invention which combines two known elements, "the question is whether there is something in the prior art as a whole to suggest the desirability, and thus the obviousness, of making the combination." In re Beattie, 974 F.2d 1309, 1311-12 (Fed. Cir. 1992) (quoting Lindemann Maschinenfabrik GMBH v. Am. Hoist & Derrick Co., 730 F.2d 1452, 1462 (Fed. Cir. 1984)). An invention will not be rendered obvious merely by combining teachings found in the prior art. There must be some suggestion or incentive in the prior art to make the combination. The prior art must suggest that the combination would have a reasonable likelihood of success. In re Bolduc, 1992 U.S. App. LEXIS 2480 (Fed. Cir., 1992). The Applicant is aware of no prior art that suggests a reasonable likelihood of success associated with the combination of titanium, aluminum and nitride in a polish stop layer. More importantly, the Examiner has not met the proper burden of proving that the referenced prior art sufficiently suggest otherwise. Accordingly, the rejection under 35 USC 103(a) should be withdrawn.

8. APPENDICES

A claims appendix containing a copy of the claims involved in this appeal is

provided herewith in accordance with 37 CFR 41.37(c)(1)(viii). The evidence appendix provided in accordance with 37 CFR 41.37(c)(1)(ix) contains no evidence because no such evidence is relied upon by the appellant in this appeal. The related proceedings appendix provided in accordance with 37 CFR 41.37(c)(1)(x) contains no citations because no such related proceeding is identified herein under 37 CFR 41.37(c)(1)(ii).

Respectfully submitted,

Beg. No. 27,115

Beusse Brownlee Wolter Mora & Maire, P.A.

390 N. Orange Avenue, Suite 2500

Orlando, FL 32801 (407) 926-7701

APPENDIX OF CLAIMS ON APPEAL 37 CFR 41.37(c)(1)(viii)

- 1. (Amended) A semiconductor structure comprising:
- a substrate having a device feature formed thereon;
- a dielectric layer disposed over said substrate and device feature and having at least one contact hole formed therein;
- a polish stop layer disposed over the dielectric layer and extending within the contact hole:
- a layer of metal disposed over the polish stop layer within the contact hole and forming a plug; and

wherein said polish stop layer comprises titanium aluminum nitride.

- 2. (Amended) The semiconductor structure of claim 1 and including a metal coating under said dielectric layer; said metal coating comprising a compound of titanium nitride and aluminum.
- 3. (Amended) The semiconductor structure of claim 2 wherein the dielectric comprises a silicon oxide.
- 4. The semiconductor structure of claim 3, wherein the metal coating comprises an anti-reflective coating.
- 5. (Amended) The semiconductor structure of claim 1, wherein the polish stop layer comprises titanium aluminum nitride with between about 5 and 20 percent by weight of aluminum.
- 7. The semiconductor structure of claim 2, wherein the metal coating comprises about 5 to 20 percent by weight of aluminum.

- 21. A semiconductor structure comprising:
- a metal layer disposed on a substrate;
- a layer of titanium aluminum nitride disposed on the metal layer;
- a dielectric layer disposed on the layer of titanium aluminum nitride;
- a patterned layer of photoresist disposed on the dielectric layer exposing a selected portion of the dielectric layer to an etching process;

4079267720

wherein the layer of titanium aluminum nitride functions as an etch stop layer upon removal of the selected portion of the dielectric layer to prevent the etching process from compromising the underlying metal layer.

EVIDENCE APPENDIX 37 CFR 41.37(c)(1)(ix)

No such evidence is relied upon by the appellant in the appeal.

RELATED PROCEEDINGS APPENDIX 37 CFR 41.37(c)(1)(x)

No such related proceeding is identified herein under 37 CFR 41.37(c)(1)(ii).